



PLUG VALVES

TYPE	: NON LUBRICATED - TAPER PORT REGULAR BORE
PRESSURE RATING	: 150#, 300#, 600#, PN 16, PN 40
DESIGN STANDARD	: API 599 / BS 5353
TESTING STANDARD	: BS EN 12266-1
FACE TO FACE	: ANSI B 16. 10, DIN 3202
END CONNECTION	: FLANGED, SCREWED, SOCKET WELD, BUTT WELD
PORT OPTIONS	: 2 - WAY, 3 - WAY, 4 - WAY & 5 - WAY PARTIAL JACKET, FULLY JACKETED SAMPLING, CAGE CONTROLLED
OPERATION	: HAND LEVER / WRENCH / GEAR / ACTUATOR
SIZE	: 15 MM TO 300 MM
M.O.C	: DI / WCB / CF8 / CF8M / CF3M / CN7M & OTHER ALLOYS

QUALITY VALVES YOU CAN RELY ON, ALWAYS.

Valco

ENGINEERING CORPORATION (HOUSE OF INDUSTRIAL VALVES)

Registered Office : 202, Chheda Bhavan, Surat Street, Near Masjid Station (E), Mumbai - 400 009, INDIA • Tel.: +91 - 22 - 2348 3751

Branch Office : 405, Man-Ratna Business Park, Opp. Foodspot, Tilak Road, Ghatkopar (E), Mumbai - 400 077, INDIA • Tel.: +91 - 22 - 2508 3751 / 52 / 53 • Fax : +91 - 22 - 2508 3754

E-mail : sales@valcoexports.com • Website : www.valcoexports.com